

High Speed Double Twist Bunching Machine (300mm)



Full automatic double-twist type wire twist machine, strengthening design of the traction system, can twist 1mm² copper wire, it can also apply on the core wire pair twisted or small core wire cabling.



8800808387 , 8882593893



C45 sec 5, Bawana IDC, New Delhi (110039)



www.tksindustries.in



info@tksindustries.in turnkeysolutionsindustries@gmail.com

TECHNICAL SPECIFICATIONS AND PARAMETERS

MODEL	TKS-300
Wire spool Max size(Dia x length)	Φ315×220
Twisted copper wire Max section	0.05mm ² -1.0mm ²
Twisted copper diameter	0.04-0.10mm
Twist pitch range	1.15-11.24 mm
Twisting direction	"S" or "Z" direction
Twist bow RPM	0-3500, infinite adjustable
Twist bow material	Spring steel tape
Injection Rate	84 cc/s
Twist bow material	Spring steel tape
conductor elements on bow	Porcelain or porcelain + pulley guide
Motor	4.0kw, frequency adjust speed
Take-up tension mechanism	Spring clutch control
Wire spool up fall structure	manual-hydraulic
Bearing	Japan NSK
Spindle height above the ground	860mm
Machine size	L2100 x W1040x H900mm
Machine net weight	800 KG
Power	3 Phase 380V, 50Hz
Machine installation place altitude	≤1000mm
Machine room temperature	≤40°C
Input wire direction	Machine right wire input